

12-13-99

A

## THOMASON, MOSER &amp; PATTERSON

ATTORNEYS AT LAW

THE GALLERIA  
2 BRIDGE AVENUE  
POST OFFICE BOX 8160  
RED BANK, NEW JERSEY 07701  
TELEPHONE (732) 530-9404  
TELEFAX (732) 530-9808

12/10/99  
jc525 U.S. PTO

## PATENT APPLICATION

Assistant Commissioner for Patents  
Box **Patent Application**  
Washington, D. C. 20231

Sir:

jc564 U.S. PTO  
09/458896  
12/10/99

Enclosed herewith for filing is the following **utility patent application which claims priority to U.S. Provisional Application, serial no. 60/127,126, filed March 31, 1999.**

Applicant(s): **Michael C. Bertram, Tobie J. La Rocca**

Title of application: **METHOD AND APPARATUS FOR INJECTING INFORMATION ASSETS INTO A CONTENT STREAM**

Pages of specification: 19 total (15 + 3 pages of claims and 1 page abstract)

Sheets of drawings: 3

Executed on: 12/8/99 Docket No.: **DIVA 038**

## PATENT APPLICATION FILING FEE CALCULATION

	<u>No. Filed</u>	<u>Less</u>	<u>Rate/Claim</u>	<u>Fee</u>
Total Claims	17	-20	0 x \$78.00	<u>\$ 00.00</u>
Independent Claims	2	-3	0 x \$18.00	<u>\$ 00.00</u>
Minimum Filing Fee				\$760.00
Multiple Dependency Fee (if applicable - \$270.00)				<u>\$ 00.00</u>
50% Reduction for Small Entity (Independent Inventor, Non-profit Corporation, or Small Business Concern) - appropriate verified statement attached				- <u>\$380.00</u>

TOTAL FILING FEE

\$380.00

Kindly charge the entire and/or any additional filing fee, as appropriate, to deposit account number 20-0782. To facilitate that charge, a duplicate copy of this letter is enclosed herewith.

Also enclosed herewith for filing in connection with the enclosed application are:

       Oath;  
XX Declaration and Power of Attorney;  
       Disclosure Statement;  
       Letter referencing previously filed disclosure document; number                  filed                 ;  
XX Verified Statement claiming small entity status;  
XX An assignment of the application to:  
            DIVA SYSTEMS CORPORATION;  
XX Claim(s) to priority - U.S. Provisional Application  
            Serial Number                      Filing date  
            60/127,126                      March 31, 1999  
       A certified copy of a                  patent application or inventor's certificate, filed                  and serial no.                 , upon which a claim to priority is made;  
       Other:   

Respectfully submitted,

12/10/99

E J Wall  
Eamon J. Wall, Attorney  
Reg. No. 39,414

Thomason, Moser & Patterson, LLP  
Attorneys at Law  
2-40 Bridge Avenue  
P.O. Box 8160  
Red Bank, NJ 07701

\*\*\*EXPRESS MAIL CERTIFICATION\*\*\*

"Express Mail" mailing label number: **EL530945609US**

Date of deposit: **12/10/99**

I hereby certify that this patent application and related papers is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

*Laura E Crater*

Signature of person mailing paper or fee

**LAURA E CRATER**

Name of person mailing paper or fee

U.S. POSTAL SERVICE  
EXPRESS MAIL CERTIFICATION  
POSTAGE WILL BE PAID BY ADDRESSEE  
NO POSTAGE  
NECESSARY  
IF MAILED  
IN THE  
UNITED STATES  
FIRST CLASS  
PERMIT NO. 1000  
WASHINGTON, D.C.

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS (37 CFR 1.9(f) AND 1.27 (c)) - SMALL BUSINESS CONCERN			Docket No. 533/038
Serial No.	Filing Date	Patent No.	Issue Date
Applicant/ Patentee: MichaelC. Bertram and Tobie J. LaRocca			
Invention: METHOD AND APPARATUS FOR INJECTING INFORMATION ASSETS INTO A CONTENT STREAM			
<p>I hereby declare that I am:</p> <p><input type="checkbox"/> the owner of the small business concern identified below:</p> <p><input checked="" type="checkbox"/> an official of the small business concern empowered to act on behalf of the concern identified below:</p> <p>NAME OF CONCERN: <u>DIVA Systems Corporation</u></p> <p>ADDRESS OF CONCERN: <u>800 Saginaw Drive, Redwood City, CA 94063</u></p> <p>I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.</p> <p>I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the above identified invention described in:</p> <p><input checked="" type="checkbox"/> the specification filed herewith with title as listed above.</p> <p><input type="checkbox"/> the application identified above.</p> <p><input type="checkbox"/> the patent identified above.</p> <p>If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed on the next page and no rights to the invention are held by any person, other than the inventor, who could not qualify as an independent inventor under 37 CFR 1.9(c) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).</p>			

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ no such person, concern or organization exists.  
☐ each such person, concern or organization is listed below.

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING:

Stephanie A. Storms

TITLE OF PERSON SIGNING

OTHER THAN OWNER:

Senior Vice President/General Counsel

ADDRESS OF PERSON SIGNING:

c/o DIVA Systems Corporation800 Saginaw DriveRedwood City, CA 94063

SIGNATURE:

Stephanie A. Storms

DATE:

12/8/99

## **METHOD AND APPARATUS FOR INJECTING INFORMATION ASSETS INTO A CONTENT STREAM**

### **CROSS REFERENCE TO RELATED APPLICATIONS**

5           This application claims benefit of U.S. Provisional Patent Application  
Serial Number 60/127,126 (attorney docket number 038), which was filed on  
March 31, 1999 and is incorporated herein by reference in its entirety.

### **BACKGROUND OF THE INVENTION**

10

#### **1. Field of the Invention**

15

The present invention relates to an information distribution system  
such as a video-on-demand (VOD) system. More particularly, the present  
invention relates to a method and apparatus for processing content and  
other assets such that the other assets may be injected into a subsequent  
content stream.

20

#### **2. Description of the Background Art**

25

Information distribution systems, such as video on demand (VOD)  
system providing content encoded according to the various Moving Pictures  
Experts Group (MPEG) standards are known. For example, a first standard  
known as MPEG-1 refers to ISO/IEC standards 11172, which is  
incorporated herein by reference in its entirety. A second standard known  
as MPEG-2 refers to ISO/IEC standards 13818, which is incorporated herein  
by reference in its entirety. Additionally, a compressed digital video system  
is described in the Advanced Television Systems Committee (ATSC) digital  
television standard document A/53, incorporated herein by reference.

30

An interactive information distribution system provided by DIVA  
Systems Corporation of Redwood City, California is described in more detail  
in U.S. Patent Application Serial No. 08/984,710, filed on December 3, 1997  
and incorporated herein by reference in its entirety. Users or subscribers to  
the DIVA system select information offerings using a "Navigator"

functionality, which is described in more detail in U.S. Patent Application Serial No. 08/984,427, filed December 3, 1997 and incorporated herein by reference in its entirety. Briefly, the Navigator utilizes a combination of MPEG content (such as MPEG video content and related MPEG audio content) and Navigator asset data to provide viewers with a means of selecting and ordering services. Navigator assets include bitmaps and navigation control scripts. As the set top box user is "navigating," the set top box extracts the asset data from the transport stream and uses that data to provide bitmap overlays on top of the MPEG content. The control data within the assets is used to define the layout of the screen and to take actions based on viewer input.

Assets, such as the aforementioned Navigator assets, are typically packaged as MPEG transport packets that are multiplexed along with content-representative MPEG packets to produce a single MPEG transport stream file. The file is then transported to and stored on each of, possibly, many servers for subsequent transmission to the users' set top boxes.

Unfortunately, embedding assets such as Navigation assets within the content places a severe limitation on changes to the assets. For example, if a bitmap asset must be changed to provide new graphic data, the content files for all navigation screens using that bitmap need to be re-multiplexed, redistributed, and re-loaded onto all servers. Additionally, the multiplexing of the Navigation assets and content results in a duplication of the Navigation asset data within each of a plurality of content streams including the data.

Therefore, it is seen to be desirable to provide a method and apparatus for inserting assets, such as navigation assets, into a content stream in a manner avoiding the above-described problems.

### SUMMARY OF THE INVENTION

The disadvantages heretofore associated with the prior art are overcome by the present invention of a method and apparatus for transport encoding asset data and content data, multiplexing the transport encoded content data with a plurality of NULL transport packets to provide "place holder" for the asset data transport packets, and replacing the NULL

transport packets with asset data transport packets prior to transmitting the multiplexed transport stream to a set top box.

Specifically, in an information distribution system providing content data and asset data to at least one subscriber, an apparatus according to the invention comprises: a NULL packet inserter, for inserting NULL transport packets within a transport stream including content packets; and a transport processor, for replacing at least some of the NULL packets with asset packets to produce a transport stream including content packets and asset packets.

### BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the present invention can be readily understood by considering the following detailed description in conjunction with the accompanying drawings, in which:

FIG. 1 depicts a high level block diagram of an interactive information distribution system;

FIG. 2 depicts a graphical representation of several packetized streams useful in understanding the invention; and

FIG. 3 depicts a flow diagram of a method for processing content and asset information according to the invention.

To facilitate understanding, identical reference numerals have been used, where possible, to designate identical elements that are common to the figures.

### DETAILED DESCRIPTION

While the invention will be primarily described within the context of an interactive information distribution system, it should be noted that the invention has broad applicability to any system in which a data stream generated by combining fixed packet length data sub-streams is subject to regeneration due to, illustratively, modifications or changes made to one of the data sub-streams.

FIG. 1 depicts a high level block diagram of an interactive information distribution system. Specifically, FIG. 1 depicts a high level block diagram of an interactive information distribution system 100



containing the present invention. The system 100 contains service provider equipment 102, a distribution network 104 and subscriber equipment 106<sub>n</sub>, where n is an integer greater than zero.

5 The service provider equipment 102 comprises a plurality of asset sources 110, a first transport packetizer 120, an asset storage module 125, an encoded content source 130, a second transport packetizer 135 including a null packet inserter 135-NP, a content storage module 140 and a session controller 145 including a mapping data memory region 145-MD, a count memory region 145-C and a rate memory region 145-R. The functionality of  
10 the service provider equipment 102 may be divided into those functions typically provided by a content development facility (CDF) 102A and those functions provided by an interactive information distribution system (IIDS) 102B. A content development facility receives encoded content from, for example, a content encoding facility where Navigation assets and/or other  
15 assets are developed or aggregated. The CDF formats the content and assets into, for example, MPEG-2 transport stream files and distributes the resultant files to IIDS locations. The CDF functionality comprises the asset sources 110, the first transport packetizer 120, the encoded content source 130 and the second transport packetizer 135. The operation of the CDF  
20 102A and IIDS 102B will be described within the context of a system 100 including all the relevant functions. However, it shall be noted that the CDF functions may be implemented in a CDF that is physically remote from the remaining functions of the system 100. The CDF functions may also be performed prior to the actual need for the assets and/or content.

25 The service provider equipment 102 processes content data and asset data to provide, respectively, a content data transport stream CONTENT and an asset data transport stream ASSETS. The asset data transport stream ASSETS includes a plurality of transport packets carrying asset data. The content data transport stream CONTENT includes a plurality of  
30 NULL transport packets interspersed with content transport packets such that the NULL packets “reserve” a portion of the asset data stream sufficient to accommodate the asset data packets within the asset data stream ASSETS. The service provider equipment 102, in response to a subscriber request for a content stream, provides a version of the requested

content stream in which some or all of the NULL packets have been replaced by asset data packets. In this manner, the service provider equipment 102 is able to adapt the asset data provided to a subscriber without reprocessing the content data.

5       The asset sources comprise, illustratively, bit map imagery 110-1, control scripts 110-2 and other assets 110-3. The bit map imagery 110-1, control scripts 110-2 and other assets 110-3 are provided to the first transport packetizer 120 via respective stream or signal paths A1, A2 and A3. The assets may comprise, e.g., Navigation assets that are used by a set  
10   top terminal to interactively navigate or view the offerings of the information distribution system 100. The first transport packetizer 120 packages the received asset streams A1-A3 into appropriate MPEG streams, such as video streams, audio streams, data streams and the like to produce a transport stream TA, illustratively an MPEG-2 transport stream, that is  
15   coupled to the asset storage module 125. Specifically, the transport stream TA (including packaged assets) is distributed from the CDF 102A to the asset storage module 125 of the IIDS 102B. The asset storage module 125 communicates with the session controller 145 via an asset control signal ASC to provide storage location information associated with each stored  
20   asset stream.

The encoded content source 130, illustratively a means of receiving MPEG-2 encoded content and other content from a studio or other source of content, provides a content stream C to the second transport packetizer 135.

25       The second transport packetizer 135 packetizes the content stream C to produce a transport stream TC, illustratively an MPEG-2 transport stream, that is coupled to the content storage module 140. In response to a control signal RESERVED BANDWIDTH, the null packet inserter 135-NP of the second transport packetizer 135 operates to intersperse NULL packets with the content packets within the content transport stream TC.

30       The number of NULL packets interspersed with the content data packets “reserves” a portion of the asset data stream sufficient to, ideally, accommodate all of the asset data packets. That is, the amount of bandwidth to be reserved by interspersing NULL packets (e.g., 300 kilobits per second of a 3.6 Megabits per second bitstream) is indicated to the NULL

packet inserter 135-NP via the control signal RESERVED BANDWIDTH.  
The number of NULL packets may be predetermined or calculated.

In one embodiment of the invention a default number of NULL  
packets is inserted into the multiplexed transport stream including null  
5 packets and content packets. The default number of NULL packets may be  
fixed or may defined as a ratio (e.g., one null packet for every four content  
packets).

The session controller 145 (or session manager) provides session  
control of the information flowing to and from the content 140 and asset 125  
10 storage modules, and may be generally described as a system providing or  
controlling communications between, e.g., a cable system head-end and one  
or more set top terminals. The session controller 145 produces an asset  
storage control signal ASC for controlling and communicating with the asset  
storage module 125, a content storage control signal CSC for controlling and  
15 communicating with the content storage module 140, and a transport  
processor control signal TPC for controlling and communicating with the  
transport processor 150.

The session controller 145 communicates with the asset storage  
module 125 and content storage module 140 to determine appropriate  
20 mapping of content streams or files stored on the content storage module  
140 to asset streams or files stored on the asset storage module 125. This  
mapping information is stored within the mapping data memory portion  
145-MD of the session controller 145.

In one embodiment of the invention, the session controller 145  
25 provides an asset injection rate (AIR) signal and an asset injection count  
(AIC) signal to the transport processor 150. The asset injection rate is  
stored in the rate memory location 145-R, while the asset injection count is  
stored in the count memory location 145-C.

The asset injection rate (AIR) signal indicates to the transport  
30 processor 150 a desired rate at which asset packets should be injected into a  
content stream including NULL packets. The asset injection rate refers to  
the number of NULL packets to be utilized for asset transport. A maximum  
asset injection rate utilizes every NULL packet to transport an asset  
stream. In lower asset rates, some NULL packets are not utilized.

The an asset injection count (AIC) signal indicates to the transport processor 150 the number of times that a particular asset should be repeated. For example, in response to an AIC signal indicative of a count of three, the transport processor will insert each asset packet into the FATC  
5 three times. The three insertions may be consecutive or an entire asset stream may be injected three times.

In response to a user request for a particular content file, the session controller 145 causes the requested content file to be streamed to the transport processor 150. Additionally, the session controller 145 utilizes the  
10 mapping data 145-MD to determine which asset data stream or file (if any) is associated with the requested content stream or file. The session controller 145 causes the requested asset file to be streamed to the transport processor 150 from the asset storage module 125.

The session controller 145 sends data, such as commands, encryption  
15 keys and the like to set top boxes via a forward data channel (FDC). The session controller 145 receives data, such as information stream requests and session initiation data (set top identification, capability, and the like) via a reverse data channel (RDC). The FDC and RDC are supported by the distribution network 104 and comprise relatively low bandwidth data  
20 channels, such as 1-2 megabits per second data channels utilizing QPSK, QAM or other modulation techniques. The FDC and RDC are also known as “out of band” channels, where a relatively high bandwidth forward application transport (FAT) channel is known as an “in-band” channel.

The session controller 145 contains an interface device for sending  
25 control information via the forward data channel FDC and receiving control information via the reverse data channel RDC using so-called “out of band” carrier frequencies.

The transport processor 150 accomplishes all of the forward content channel transmission interface requirements of the system 100 of FIG. 1.  
30 Specifically, the transport processor 150 is coupled to subscriber equipment via a forward applications transport channel (FATC). The forward application transport channel (FATC) is supported by the distribution network 104 and comprises a relatively high bandwidth communications channel well suited to carrying video, audio and data such as, for example,

multiplexed MPEG-2 transport packets. The FATC is also known as the “in-band” communications channel. It should be noted that data normally conveyed to a set top box via the FDC may be included in the FATC data stream.

5       The transport processor 150 contains a multiplexer or combiner for detecting NULL packets within the content stream CONTENT, and for replacing some or all of those NULL packets with asset packets from the asset stream ASSET to form a combined content and asset stream. The transport processor 150 also contains a modulator for modulating the  
10 combined content and asset stream onto one or more carrier frequencies for transmission on the FATC, the so-called “in band” carrier frequencies.

      The distribution network 104 can be any one of a number of conventional broadband communications networks that are available such as a fiber optic network, a telephone network, existing cable television  
15 network and the like. For example, if the network is a hybrid fiber-coax network, the transmission transport technique used in both forward channels may be modeled after the Moving Pictures Expert Group (MPEG) transport protocol for the transmission of video data streams. In general, the transport mechanism for forward and reverse data channels that  
20 transport information to and from the set top terminal must be able to carry unidirectional, asynchronous packetized data such as that defined in the MPEG video and audio signal transmission protocol, and the like. There are a number of such transport protocols available.

      The subscriber equipment 106<sub>n</sub> comprises a subscriber or set top  
25 terminal or set top box 136, a display device 140 (e.g., a conventional television) and a user input device 138 (e.g., a remote control). Each set top terminal 136 receives the data streams from the FATC, demodulates the received data streams and, in the case of video streams, processes the demodulated video streams for subsequent display on the display device  
30 140. In addition, the set top terminal 106 accepts commands from the remote control input device 138 or other input device. Those commands requiring processing at the lead end are formatted, modulated, and transmitted through the distribution network 104 to the session controller 145. Typically, this transmission is accomplished through the RDC. These

commands are preferably transmitted through the same network used to transmit information to the set top terminal. However, the RDC coupling the set top terminal to the server may be a separate network, e.g., a FATC through a television cable network and a RDC through a telephone network.

5 The telephone network could also support the FDC.

The session controller 145 interprets each command sent from the set top terminal through the RDC and adapts other functional elements (e.g., the storage modules) in response to the subscriber request (e.g., send a requested movie and associated asset data).

10 Session control commands, such as navigation commands, are implemented by the session controller 145 with the set top terminal 136. Each command is implemented by the execution of central scripts by the set top terminal 136. The central scripts are transmitted to the set top terminal 136 (via the FATC) within the asset data in response to requests  
15 transmitted by the set top terminal 136 (via the RDC). It is noted that each control script includes links to other control scripts stored at the IIDS head end 102B. In this manner, set top terminal memory is conserved. The control scripts control both information sessions, such as the presentation of video to the television screen, and navigator functions, such as menus  
20 facilitating selection of a video program. The graphical data and other asset data used to provide the user interface at the set top terminal 136 comprises asset data, such as navigator asset data that is processed by the service provider equipment 102 of the present invention.

FIG. 2A depicts a graphical representation of several packetized  
25 streams useful in understanding the invention. Specifically, FIG. 2A depicts graphical representations of an asset transport stream 210, a content and NULL transport stream 220 and a content and asset transport stream 230.

The asset transport stream 210 is depicted as plurality of asset transport packets, where each transport packet includes a portion of the  
30 asset data. The asset data packets are denoted by the letter "A" within the asset stream representation 210. Illustratively, referring to the system 100 of FIG. 1, the NAVIGATION ASSETS stream provided by the asset storage module 125 to the transport processor 150 is structurally similar to the asset stream representation 210 of FIG. 2A.

The content and NULL transport stream 220 is depicted as a plurality of content data transport packets interspersed with NULL transport packets. Specifically, the content and NULL transport stream 220 comprises a repeating sequence of three content data packets followed by a single NULL packet. The content data packets are denoted by the letter “C” while the NULL packets are denoted by the NULL symbol (i.e., “Ø”).

Illustratively, referring to the system 100 of FIG. 1, the CONTENT stream provided by the content storage module 140 to the transport processor 150 is structurally similar to the content and NULL stream representation 220 of FIG. 2A.

Each of the asset data packets A in the asset transport stream 210 is associated with a corresponding NULL packet Ø in the content and NULL transport stream 220, as indicated by the correspondence arrows T1-T9.

This correspondence is depicted for illustrative purposes only, since there need not be a strict correspondence of particular asset packets to particular NULL packets. It should be noted that NULL packets may be skipped (i.e. unutilized) such that a lower “asset injection rate” is provided. That is, the rate or utilization level of the NULL packets may be reduced by not inserting asset packets into every available NULL packet. The utilization level of the NULL packets may be described in terms of a percentage of available NULL packets, a percentage of available NULL packets for a given period of time (or bandwidth), or any other convenient metric.

Moreover, asset packets may be inserted repeatedly into the asset and NULL transport stream, such that an “asset injection count” above unity is provided. That is, the entire asset packet stream may be repeatedly inserted such that a set top terminal may reacquire an asset stream that has been incorrectly acquired. NULL packets may be left unutilized, especially in the case of a relatively small asset stream.

The content and asset transport stream 230 is depicted as a plurality of content data transport packets interspersed with asset transport packets. Specifically, the content and asset transport stream 230 comprises a repeating sequence of three content data packets followed by a single asset packet. The content data packets are denoted by the letter “C” while the asset packets are denoted by letter “A.” Illustratively, referring to the

system 100 of FIG. 1, the FATC stream provided by the transport processor to the subscriber equipment 106 includes information streams that are structurally similar to the content and asset stream representation 230 of FIG. 2.

5 It should be noted that it is not necessary for each NULL packet to be replaced by an asset packet. However, it is preferable to have a sufficient number of NULL packets within the content and NULL packet stream to provide for all of the asset packets to be included in the stream provided to the subscriber. Thus, the transport processor 150 of FIG. 1 operates to  
10 replace either some or all of the NULL packets with the content and NULL packet stream to provide a content and asset stream.

FIG. 2B depicts a graphical representation of several packetized streams useful in understanding the invention. Specifically, FIG. 2B depicts graphical representations of an asset transport stream 240, a content and  
15 NULL transport stream 250, and a content and asset transport stream 260.

FIG. 2B differs from FIG. 2A in that the content and NULL transport stream 250 includes more frequently interspersed NULL packets (i.e., one NULL packet after every two content packets), and the terminal or end  
20 portion of the asset transport stream 240 is depicted. Thus, it is noted that after replacing NULL packets in the content and NULL stream 250 with asset packets found in the asset transport stream 240, the resulting content and asset transport stream 260 includes a plurality of remaining NULL packets 261, 262.

With respect to the content and NULL packet transport streams 220  
25 and 250, it is important to note that the content and NULL transport stream 250 of FIG. 2B allocates a larger portion of bandwidth to the transport of asset packets. As previously discussed, a control signal RESERVED BANDWIDTH provided to the second transport packetizer 235 is indicative of an amount of bandwidth to be reserved for the transport of  
30 asset packets. Thus, this control signal caused a higher bandwidth allocation for the content and NULL transport stream 250 than for the content and NULL transport stream 220.

FIG. 3 depicts a flow diagram of a method for processing content and asset information according to the invention. The method 300 of FIG. 3 may



be considered as several separate methods. Specifically, steps 305 through 320 define a method for processing content information, steps 305 and 330 through 335 define a method for processing asset information and steps 340 through 365 define a method for providing processed content and asset  
5 information to a set top terminal.

At step 305 the MPEG content and navigator aspects for a navigator screen are defined or created. That is, at step 305 the video information, control information and graphical information for, e.g., a navigator screen having respective control, video and graphics layer is defined or created.

10 The method 300 then proceeds to step 310.

At step 310 the MPEG content is packetized. That is, at step 310 the MPEG video information defined or created at step 305 is converted into a plurality of information packets, such as MPEG transport packets. This function may be performed by the transport packetizer 135 of the  
15 information distribution system 100 of FIG. 1. The method 300 then proceeds to step 315.

At step 315 the, illustratively, MPEG transport packets including content information are multiplexed with a plurality of null packets. A null packet comprises an MPEG transport packet having no useful information and serving the sole purpose of occupying space within an MPEG transport  
20 stream. This function may be performed by the null packet inserter 135-NP of the system 100 of FIG. 1. The method 300 then proceeds to step 320.

At step 320 the multiplexed content/null packet stream is stored in, illustratively, the content storage module 140. The method 300 then  
25 proceeds to step 340.

The above-described steps (310-320) describe the processing of the content defined or created at step 305. The asset information defined or created at step 305 is similarly processed as will now be described. It should be noted that the asset processing and content processing may occur  
30 sequentially in either order or simultaneously.

At step 330 the asset streams A1-A3 are packetized into, illustratively, MPEG-2 transport packets and multiplexed to produce a packetized asset stream TA. This function is performed by the first transport packetizer 120 of the system 100 of FIG. 1. The method 300 then

proceeds to step 335, where the packetized asset stream TA produced by the transport packetizer 120 is stored in, illustratively, the asset storage module 125. The method 200 then proceeds to step 340.

At step 340 mapping data linking the content and asset data (e.g., navigation screens, MPEG content and navigation assets) is generated. That is, mapping data used to link the multiplexed content/null packet stream of stored in the content storage module 140 to the packetized asset stream stored in the asset storage module 125 is generated such that subsequent processing of the streams by the transport processor 150 may be used to combine video, associated audio, and assets, such as navigation assets. The method 300 then proceeds to step 345.

It should be noted that the generation of mapping data is depicted as occurring after the storage of the content TC and asset TA transport streams in the asset storage 125 and content storage 140 modules respectively. However, it will be appreciated by those skilled in the art that mapping data may be produced contemporaneously with the generation of those streams.

At step 345 the method 300 waits for an set top terminal content request. That is, at step 345 the session controller 145 interacting with a subscriber terminal 136 waits for a request from that subscriber terminal for content stored within the content storage module 140. The method 300 then proceeds to step 350.

At step 350, in response to the set top terminal content request, mapping data for the requested content is retrieved from the mapping data memory portion 145-MD of the session controller 145. The retrieved mapping data is used to identify which packetized asset stream within the asset storage module 125 is associated with the content/null packet stream within the content storage module 140 that has been requested by the set top terminal. The method 300 then proceeds to step 353.

At optional step 353, the session controller 145 provides to the transport processor 150 one or both of the asset injection rate (AIR) parameter and the asset injection count (AIC) parameter. In response, the transport processor 150 adjusts the asset injection rate and/or the number of times an asset is injected (asset injection count).

At step 355 the stored multiplex/content null packet stream requested by the subscriber and the stored packetized asset stream associated by the mapping data are coupled to the transport processor 150 to be combined.

At step 360, null packets within the content/null packet stream  
5 retrieved from the content storage module 140 are replaced, as necessary, with asset packets from the packetized asset stream retrieved from the asset storage module 125 (as defined by the mapping data). Thus, in the case of a multiplexed content/null packet stream in which every, for example, fourth transport packet comprises a null packet, sufficient null  
10 packets to accommodate the asset packets retrieved from the asset storage module 125 are replaced. Ideally, every null packet will be replaced by an asset packet such that no bandwidth is wasted. However, since it is important to assure adequate levels of system performance and adequate quality of interaction from the point of view of a subscriber, it is likely that  
15 an excess number of null packets is advantageously provided such that unusually large asset streams may be accommodated without unduly degrading system performance.

At step 365 the content stream including the asset packets is provided to the subscriber terminal or STT via the appropriate physical and logical  
20 channels. These physical and logical channels are determined at the time the set top terminal establishes a session with the session controller 145.

Various modifications to the above-described embodiments are contemplated by the inventor. For example, while the asset and content storage functions are depicted in FIG. 1 as being implemented using  
25 separate asset 125 and content 140 storage modules, a single storage module may be utilized to realize these functions. Moreover, within the context of an information distribution system having a plurality of information servers, these functions may be distributed over several information servers. For example, a central or asset server may be used to  
30 hold a "gold" copy of asset data that is periodically used to update asset data stored in other servers along with content data.

It should be noted that while the function of mapping data between content and asset data is performed with respect to the depicted mapping data 145-MD element of the session controller 145, the mapping data 145-

MD may be stored in the single storage module or either of the asset and content storage modules. It is only necessary that the entity controlling the distribution of the content stream CONTENT and the asset stream ASSET utilize the mapping data 145-MD such that the asset stream appropriate to  
5 a requested content stream is provided to the transport processor 150 along with the requested content stream.

Although various embodiments which incorporate the teachings of the present invention have been shown and described in detail herein, those skilled in the art can readily devise many other varied embodiments that  
10 still incorporate these teachings.

What is claimed is:

1. In an information distribution system providing content data and asset data to at least one subscriber, apparatus comprising:
  - 5 a NULL packet inserter, for inserting NULL transport packets within a transport stream including content packets; and
  - a transport processor, for replacing at least some of said NULL packets with asset packets to produce a transport stream including content packets and asset packets.
- 10 2. The apparatus of claim 1, further comprising:
  - a first transport packetizer, for packetizing said asset data to produce said asset packets; and
  - a second transport packetizer, cooperating with said NULL packet
  - 15 inserter, for packetizing said content data and producing said transport stream including content packets.
3. The apparatus of claim 2, further comprising:
  - storage means, coupled to said transport processor, for storing said
  - 20 asset packets and said transport stream including content packets and NULL packets.
4. The apparatus of claim 1, further comprising:
  - storage means, coupled to said transport processor, for storing said
  - 25 asset packets and said transport stream including content packets and NULL packets.
5. The apparatus of claim 4, further comprising:
  - a session controller, for interacting with a subscriber to receive a
  - 30 content request;
  - said controller causing a transport stream including said requested content packets and NULL packets to be provided to said transport processor; and

said controller causing asset packets associated with said requested content to be provided to said transport processor.

6. The apparatus of claim 1, wherein said NULL packet inserter is  
5 responsive to a bandwidth reservation signal to adapt a number of NULL packets inserted into said transport stream including content packets.

7. The apparatus of claim 1, wherein said second transport packetizer  
10 provides mapping data indicative of the location of NULL packets within said transport stream including content packets and NULL packets.

8. The apparatus of claim 2, wherein:  
said transport processor is responsive to an asset rate control signal  
15 to adapt a utilization level of said NULL packets.

9. The apparatus of claim 2, wherein:  
said transport processor is responsive to an asset count signal to  
replace a plurality of NULL packets with each asset packet.

20 10. In an information distribution system providing content data and asset data to at least one subscriber, a method for processing content and asset information comprising the steps of:

inserting, within a transport stream including content packets, a  
plurality of NULL packets; and  
25 replacing at least some of said NULL packets with asset packets to produce a transport stream including content packets and asset packets.

11. The method of claim 10, wherein said asset packets have been  
processed according to the steps of:  
30 packetizing, using a transport packetizer, at least one information stream comprising an asset information stream, said asset information stream being associated with a content stream.

12. The method of claim 11, wherein said asset information stream comprises a plurality of asset information sub-streams.

13. The method of claim 10, wherein said plurality of NULL packets to be  
5 inserted into said transport stream including content packets is determined with respect to a bandwidth reservation signal.

14. The method of claim 10, further comprising the step of providing  
10 mapping data indicative of the location of NULL packets within said transport stream including content packets and NULL packets.

15. The method of claim 14, wherein said step of replacing comprises the steps of:

finding, using said mapping data, the location of a next NULL packet  
15 within said transport stream including content packets and NULL packets;  
determining, according to an asset injection rate, if said next NULL packet should be replaced by an asset packet; and

in the case of a determination that said next NULL packet should be  
replaced by an asset packet, replacing said next NULL packet with a next  
20 asset packet.

16. The method of claim 1, wherein said step of inserting said asset packets is repeated according to an asset injection count.

25 17. The method of claim 11, further comprising the steps of:  
interacting with a subscriber to receive a content request;  
retrieving a transport stream including said requested content packets and any inserted NULL packets;  
replacing at least some of said NULL packets with said asset packets;  
30 and  
transporting, to said requesting subscriber, a transport stream including said transport stream including said requested content and said inserted asset packets.

ABSTRACT

A method and apparatus for transport encoding asset data and content data, multiplexing the transport encoded content data with a plurality of NULL transport packets to provide “place holder” for the asset data transport packets, and replacing the NULL transport packets with asset data transport packets prior to transmitting the multiplexed transport stream to a set top box.






FIG. 1




FIG. 2A





FIG. 2B



305  
DEFINE / CREATE MPEG CONTENT  
AND NAVIGATOR ASSETS FOR  
NAVIGATOR SCREEN

310  
PACKETIZE MPEG CONTENT

315  
MULTIPLEX CONTENT PACKETS  
AND NULL PACKETS

320  
STORE MULTIPLEXED CONTENT / NULL  
PACKET STREAM

330  
PRODUCE  
PACKETIZED ASSET  
STREAM

335  
STORE PACKETIZED  
ASSET STREAM

340  
GENERATE MAPPING DATA TO LINK  
NAVIGATION SCREENS, MPEG CONTENT  
AND NAVIGATOR ASSETS

345  
WAIT FOR STT CONTENT REQUEST

350  
RETRIEVE MAPPING DATA FOR  
REQUESTED CONTENT

353  
NOTIFY TRANSPORT  
PROCESSOR OF AIR  
AND AIR

355  
COUPLE STORED MULTIPLEXED CONTENT / NULL PACKET STREAM  
AND STORED PACKETIZED ASSET STREAM  
TO TRANSPORT PROCESSOR

360  
REPLACE NULL PACKETS WITH ASSET PACKETS

365  
PROVIDE CONTENT STREAM INCLUDING ASSET PACKETS  
TO STT VIA APPROPRIATE PHYSICAL / LOGICAL STREAM

Atty. Dkt. No. 533/038

**COMBINED DECLARATION AND POWER OF ATTORNEY****As a below named inventor, I hereby declare that:**

This declaration is of the following type:

- ☒ original  
☐ divisional  
☐ continuation  
☐ continuation-in-part

**INVENTORSHIP IDENTIFICATION**

My residence, post office address and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**TITLE OF INVENTION**

**METHOD AND APPARATUS FOR INJECTING INFORMATION ASSETS INTO A  
CONTENT STREAM**

**SPECIFICATION IDENTIFICATION**

The specification of which:

- ☒ is attached hereto  
☐ was filed on \_\_\_\_\_, under Serial No. \_\_\_\_\_, executed on even date  
 herewith; or  
☐ Express Mail No. \_\_\_\_\_ (as Serial No. not yet known)  
 and was amended on \_\_\_\_\_ (if applicable)  
☐ was described and claimed in PCT International Application No. \_\_\_\_\_  
 filed on \_\_\_\_\_ and as amended under PCT Article 19 on \_\_\_\_\_.

**ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR**

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56, and which is material to the examination of this application; namely, information where there is a substantial likelihood that a reasonable Examiner would consider it important in deciding whether to allow the application to issue as a patent, and

- ☐ In compliance with this duty, there is attached an Information Disclosure Statement in accordance with 37 CFR §1.98.

**PRIORITY CLAIM (35 U.S.C. §119)**

I hereby claim priority benefits under Title 35, United States Code, §119, of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America or of any United States Provisional Application(s) listed below, and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one

Atty. Dkt. No. 533/038

country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

☐ No such applications have been filed.

☒ Such applications have been filed as follows:

A. Prior foreign/PCT/provisional application(s) filed within 12 mos. (6 mos. for design) prior to this application, and any priority claims under 35 U.S.C. §119

<u>Country/PCT</u>	<u>Application No</u>	<u>Date Filed</u>	<u>Priority Claimed</u>
U.S.A.	Provisional 60/127,126	3/31/99	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO

B. All foreign application(s), if any, filed more than 12 mos. (6 mos for design) prior to this U.S. application

Country:

Application No:

Filing date:

**PRIOR U.S. APPLICATION(S) FOR WHICH BENEFIT  
UNDER 35 U.S.C. §120 IS CLAIMED**

<u>Serial No.</u>	<u>Filing Date</u>	<u>Status</u>		
		<u>Patented</u>	<u>Pending</u>	<u>Abandoned</u>
		<input type="checkbox"/> patented	<input type="checkbox"/> pending	<input type="checkbox"/> abandoned
		<input type="checkbox"/> patented	<input type="checkbox"/> pending	<input type="checkbox"/> abandoned
		<input type="checkbox"/> patented	<input type="checkbox"/> pending	<input type="checkbox"/> abandoned

**POWER OF ATTORNEY**

I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Charles Lee Thomason	Reg. No. 31,431	Eamon J. Wall	Reg. No. 39,414
Raymond R. Moser Jr.	Reg. No. 34,682	R. Gale Rhodes Jr.	Reg. No. 19833
Joseph Pagnotta	Reg. No. 39,322	Wan Yee Cheung	Reg. No. 42,410
Kin-Wah Tong	Reg. No. 39,400		

**Send correspondence to:**

Thomason, Moser & Patterson LLP  
The Galleria - 2d Floor  
2-40 Bridge Ave.  
Post Office Box 8160  
Red Bank, NJ 07701

**Direct telephone calls to:**

Eamon J. Wall  
732-530-9404

**DECLARATION**

*I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and, further, that these*

Atty. Dkt. No. 533/038

*statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Sec. 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patents issued thereon.*

Full name of **sole or first** inventor:

Inventor's signature: Michael C. Bertram Date: 12/8/99  
Residence: \_\_\_\_\_  
Post Office Address: 417-17 Camille Circle, San Jose, CA 95134

Country of Citizenship: USAFull name of **second** inventor:

Inventor's signature: Tobie J. LaRocca Date: 12/8/99  
Residence: \_\_\_\_\_  
Post Office Address: 3352 Nesta Drive, San Jose, CA 95118

Country of Citizenship: USAFull name of **third** inventor:

Inventor's signature: \_\_\_\_\_ Date: \_\_\_\_\_  
Residence: \_\_\_\_\_  
Post Office Address: \_\_\_\_\_

Country of Citizenship: \_\_\_\_\_

Full name of **fourth** inventor:

Inventor's signature: \_\_\_\_\_ Date: \_\_\_\_\_  
Residence: \_\_\_\_\_  
Post Office Address: \_\_\_\_\_

Country of Citizenship: \_\_\_\_\_

Full name of **fifth** inventor:

Inventor's signature: \_\_\_\_\_ Date: \_\_\_\_\_  
Residence: \_\_\_\_\_  
Post Office Address: \_\_\_\_\_

Country of Citizenship: \_\_\_\_\_

Full name of **sixth** inventor:

Inventor's signature: \_\_\_\_\_ Date: \_\_\_\_\_  
Residence: \_\_\_\_\_  
Post Office Address: \_\_\_\_\_

Country of Citizenship: \_\_\_\_\_